

nordicidmerlin

Nordic ID Merlin is a robust, high performance best-in-class handheld RFID reader for professional use with future-proof, backwards-compatible design. Ideal for a variety of production uses and commercial applications. Nordic ID Merlin is first and foremost a working tool. It's designed for ruggedness and reliability, and built to operate all day long on a single charge. Great ergonomic design ensures that it fits comfortably in the hand, while superior functionality makes it a valuable tool— simply because it makes work so much easier.

Nordic ID Merlin -series include: Nordic ID Merlin UHF RFID Cross Dipole, Nordic ID Merlin UHF RFID, Nordic ID Merlin HF RFID Blade, Nordic ID Merlin HF RFID and Nordic ID Merlin. Each device is flexible by design, allowing customers to select from various identification and communication options to meet their organization's specific needs.



PRODUCT VERSIONS

NORDIC ID MERLIN
UHF RFID CROSS DIPOLE



NORDIC ID MERLIN
UHF RFID



NORDIC ID MERLIN
HF RFID BLADE



NORDIC ID MERLIN
HF RFID



NORDIC ID MERLIN



LASER
OR
2D
IMAGER

3G
UMTS / HSDPA
900/2100 MHz

GPS
Assisted GPS

WLAN
802.11 a/b/g/n
WPA2

BLUETOOTH
2.0
+ EDR Class 2

WINDOWS
CE 6.0

USB &
ETHERNET
via Charger

RFID IDENTIFICATION

NORDIC ID MERLIN
UHF RFID Cross Dipole

Supported standard: ISO 18000-6C (EPC Class 1 Gen 2)
Frequency ETSI 865.6 - 867.6 MHz or FCC/IC 902 - 928 MHz
RF Power: ERP +30 dBm (1W) / Nominal reading distance: 5 m
One-Series: RF Power: ERP +33 dBm (2W) / Nominal reading distance: 7 m
Typical reading speed: 200 tags per second
Software controlled antenna polarization
Horizontal, vertical or cross-polarized

NORDIC ID MERLIN
UHF RFID

Supported standard: ISO 18000-6C (EPC Class 1 Gen 2)
Frequency ETSI 865.6 - 867.6 MHz or FCC/IC 902 - 928 MHz
RF Power: ERP +27 dBm (0.5W)
Nominal reading distance: 2.5 m
Typical reading speed: 200 tags per second
Horizontal linear polarized

NORDIC ID MERLIN
HF RFID BLADE

Supported standard: ISO15693
RF Power: 13.56MHz, 1W
Nominal reading distance: 0-40 cm
Reading speed: up to 40 tags per second

NORDIC ID MERLIN
HF RFID

Supported standard: ISO15693
RF Power: 13.56MHz, 1W
Nominal reading distance: 0-30 cm
Reading speed: up to 40 tags per second

LASER IDENTIFICATION

1D laser scanner

All major 1D bar codes
Adaptive Auto-Range Laser (standard-, long- and auto-range)
Normal, hold to aim and hold down modes
Enhanced aiming mode (automatic switching between scan line / aiming dot)
Configurable scan alert sounds

2D imager

All major 1D and 2D codes
High visibility LED aimer
2 character pre and post fixes, padding, replacement
Video preview
Configurable scan alert sounds

PRODUCT HIGHLIGHTS

- Multiple identification and communication options
- High performance UHF RFID
- Robust and outdoor usable
- Ergonomic and light weight
- Individual button light control
- Clear and bright screen
- Clear keypad layout
- Customer specific SW configurations
- Latest and most secure operating system
- Long operating hours
- 2 years warranty and 5+ years product support

ACCESSORIES

- Desktop/Vehicle charging cradle with USB connection including power supply (EU, UK, US)
- DC adapter with cigarette lighter connector
- Desktop charging cradle with USB and Ethernet
- 4 slot desktop charger including power supply
- 4 slot battery charger including power supply (EU, UK, US)
- Holsters and protective covers
- Pistol grip (includes battery)
- Available in custom colours

PREINSTALLED APPLICATIONS

MICROSOFT APPLICATIONS:

- Internet Explorer web browser
- Wordpad
- Microsoft® Silverlight™
- IE with Adobe® Flash® Lite

PLATFORM	
CPU	ARM11 532 MHz
Operating system	Microsoft® Windows® Embedded CE 6.0
Memory	256 MB DDR RAM 288 MB Flash (256 MB user accessible) microSD card slot (SDHC compatible)
USER INTERFACE	
Display	3,5" QVGA touch screen, 240 x 320 pixels, 262k colours Adjustable LED backlight, Daylight readable
Keypad	Numeric (alpha) keypad 29 distinguished buttons: 0-9 (alpha), scan, ok, del, tab, esc, shift, alt, 3 mode keys, 6 navigation keys Keyboard backlight with individual control for each key
Signals and indicators	Buzzer for audible signals (RTTTL support) Battery charging indicator LED Programmable LED
COMMUNICATION	
Wireless WAN	3G UMTS / HSDPA (900/2100 MHz) GPRS / EDGE (900/1800 MHz) (optional)
GPS	Assisted GPS (optional)
Wireless LAN	IEEE 802.11 a/b/g/n
WLAN security	Standards: WEP, WPA, WPA2 (802.11i) Encryption: WEP, TKIP, AES
Wireless PAN	Bluetooth 2.0 + EDR, Class 2
LAN	Ethernet 10/100 via charger (optional)
PAN	USB via charger
POWER	
Battery	Rechargeable, removable Lithium-Ion battery pack 2600 mAh @ 7.4V 4800 mAh @ 7.4V with pistol grip Up to 30 h in intensive use (standard battery)
Charging	Desktop charging cradle with USB connection Desktop charging cradle with spare battery charging slot Typical charging time: 2,5 h (0 to 90 %) and 5 h (0 to 100 %)
External power supply	AC adapter for desktop charger: input 100-240 VAC, 1A, 50-60 Hz / output 24 VDC, 1.3A, 31.2 W / Power cable for EU, UK or US
Backup battery / batteries	Back-up battery for RAM: maintains memory contents for 8 hours Back-up battery for real-time clock: keeps time for 200 days
SIZE AND WEIGHT	
Dimensions	Nordic ID Merlin UHF RFID Cross Dipole (H) 250 x (W) 105 x (D) 175 mm Nordic ID Merlin UHF RFID (H) 250 x (W) 90 x (D) 47 mm Nordic ID Merlin HF RFID Blade (H) 340 x (W) 105 x (D) 265 mm Nordic ID Merlin HF RFID (H) 250 x (W) 90 x (D) 47 mm Nordic ID Merlin (H) 230 x (W) 90 x (D) 47 mm
Weight	Nordic ID Merlin UHF RFID Cross Dipole ~ 750 g Nordic ID Merlin UHF RFID ~ 550 g Nordic ID Merlin HF RFID Blade ~ 750 g Nordic ID Merlin HF RFID ~ 550 g Nordic ID Merlin ~ 450 g
DROP AND SHOCK	
Drop and impact resistance (drops onto concrete)	1.6 m (all except HF RFID Blade: 1.2 m)
Tumble	0,5 m ~500 tumbles (all except HF RFID Blade: n/a) 1 m ~250 tumbles (all except HF RFID Blade: n/a)
ESD	Contacts +/- 4kVdc Air discharge +/- 8kVdc
ENVIRONMENT	
Environmental sealing	IP54 - dust and water splash protected (all except HF RFID Blade: n/a)
Temperature	Operating -20° to +55° C Storage -20° to +60° C Charging 0° to +45° C
Relative humidity	10% to 95% non-condensing

NORDIC ID APPLICATIONS:

- Display rotate
- Registry backup
- IP config
- Version tool
- NID Menu

CONTROL PANEL APPLET:

- NID Autostart: automatic start of application after network connection is established
- NID Backlight: backlight brightness
- NID Indicators: battery level and signal level indicators
- NID Backlight: keyboard & display brightness level
- NID Keypad: keyboard mapping
- NID LinkWatchdog: connection monitoring
- NID Menu: application manager
- NID Powerbutton: power button mapping
- NID Scanner: barcode type settings
- NID SNTP Service: network time synchronization
- NID Touch screen: disable/enable
- NID Trigger button: Trigger button mapping
- NID WWAN settings

OPTIONAL APPLICATIONS

- Nordic ID Thin Client: RF-series emulation
- Naurtech CEM: terminal emulation client
- Naurtech SAP browser
- Netop remote management

SOFTWARE DEVELOPMENT ENVIRONMENT

For all developers:

- USB driver and Microsoft Active sync + remote display
- Nordic ID MHL hardware abstraction layer
- Nordic ID UHF RFID API
- Nordic ID Sample applications and source code
- Nordic ID Customizer

FOR .NET (C#, VB ETC)

- Microsoft Visual Studio 2005 and 2008
- .NET Compact Framework 2.0 and 3.5
- Nordic ID SDK
- MHL API wrapper for .NET
- OpenCF .NET

FOR C++

- Nordic ID SDK
- NUR API
- MHL API
- Header file

FOR HTML

- Nordic ID Sample applications

ENVIRONMENT

- Free support during and after 2 year warranty time
- Maintenance service and extended maintenance contract
- Software customization and development support
- Technology, product and integration training
- Technology and project consultation
- Project management services

All information is subject to change without prior notice.



NORDIC ID HEADQUARTERS

Myllyojankatu 2 A
FI-24100 Salo
FINLAND
tel. +358 2 727 7700
fax +358 2 727 7720
info@nordicid.com
www.nordicid.com

GERMANY

Nordic ID GmbH
Bielefeld, Germany
tel. +49 521/557717-0
fax +49 521/557717-10
info@nordicid.de
www.nordicid.de

BENELUX

Alphen aan den Rijn
The Netherlands
tel. +31 172 233 097
fax +31 172 475 653
info@nordicid.nl
www.nordicid.nl